

5' Wide Multi-Purpose Standard Specifications

	5 x 8	5 x 8	5 x 10	5 x 10 TA	5 x 12	5 x 12 TA
Overall Length	12' 4"	12' 4"	14' 4"	14' 4"	16' 4"	16' 4"
Width	76"	81"	81"	81"	81"	81"
Height	70 1/2"	78 1/2"	78 1/2"	90 1/2"	78 1/2"	90 1/2"
Interior Length	8' 6"	8' 6"	10' 6"	10' 6"	12' 6"	12' 6"
Width	57 1/2"	57 1/2"	57 1/2"	57 1/2"	57 1/2"	57 1/2"
Height	48"	60"	60"	72"	60"	72"
Platform/Hitch Height	19 1/2"	17"	17"	17"	17"	17"
Axles	Spring	Spring/Torsion	Spring/Torsion	Spring/Torsion	Spring/Torsion	Spring/Torsion
Brakes	N/A	N/A	N/A	Electric	N/A	Electric
Frame	2" x 3"	2" x 3"	2" x 3"	2" x 3"	2" x 3"	2" x 3"
Tire Size	B78/13	ST205/75D14	ST205/75D14	ST205/75D14	ST205/75D14	ST205/75D14
Hitch Ball Size	2"	2"	2"	2 5/16"	2"	2 5/16"
Curb Weight (#)	800	900	960	1310	1020	1370
Hitch Weight (#)	110	120	130	150	140	170
GVWR (#)	2,000	3,500	3,500	7,000	3,500	7,000
Payload Capacity (#)	1,200	2,600	2,540	5,690	2,480	5,630
Rear Doors	Double	Double	Double	Double	Double	Double
Opening Width	50"	50"	50"	50"	50"	50"
Opening Height	41 1/2"	53 1/2"	53 1/2"	65 1/2"	53 1/2"	65 1/2"
Exterior	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth
Floor (24" O.C.)	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech
Sidewalls (16" O.C.)	3/16" Luan	3/16" Luan	3/16" Luan	3/8" Plywood	3/16" Luan	3/8" Plywood

Additional Standard Features found on all models

- * Fiberglass Front Cap
- * ICC Lighting
- * Safety Chains
- * Safety Breakaway Kit on Electric Brake Units
- * 16" On-Center Wall Studs
- * Brushed Aluminum Fenders
- * Camlocked Rear Doors
- * Seamless Aluminum Roof
 - = .019"
 - = .023 on Widebody
- * Steel Frame Base
 - = 11 GAUGE = 1/8"
 - Roof = 16 GAUGE = 1/16"
 - Sidewalls = 18 GAUGE = 3/64"

ADD 180# FOR A LIGHT WEIGHT RAMP DOOR
 ADD 20# FOR EVERY 6" ADDITIONAL HEIGHT