

6' Wide Multi-Purpose Standard Specifications

	6 x 8	6 x 8 TA	6 x 10	6 x 10 TA	6 x 12	6 x 12 TA	6 x 14	6 x 14 TA	6 x 16 TA	6 x 18 TA
Overall Length	12' 5"	12' 5"	14' 5"	14' 5"	16' 5"	16' 5"	18' 5"	18' 5"	20' 5"	22' 5"
Width	93"	93"	93"	93"	93"	93"	93"	93"	93"	93"
Height	87"	93"	87"	93"	87"	93"	87"	93"	94"	94"
Interior Length	8' 8"	8' 8"	10' 8"	10' 8"	12' 8"	12' 8"	14' 8"	14' 8"	16' 8"	18' 8"
Width	69 1/2"	69 1/2"	69 1/2"	69 1/2"	69 1/2"	69 1/2"	69 1/2"	69 1/2"	69 1/2"	69 1/2"
Height	66"	72"	66"	72"	66"	72"	66"	72"	72"	72"
Platform/Hitch Height	19"	19"	19"	19"	19"	19"	19"	19"	20"	20"
Axles	Spring/Torsion	Spring/Torsion	Spring/Torsion	Spring/Torsion	Spring/Torsion	Spring/Torsion	Spring/Torsion	Spring/Torsion	Spring/Torsion	Spring/Torsion
Brakes	N/A	Electric	N/A	Electric	N/A	Electric	N/A	Electric	Electric	Electric
Frame	2" x 4"	2" x 4"	2" x 4"	2" x 4"	2" x 4"	2" x 4"	2" x 4"	2" x 4"	2" x 5"	2" x 5"
Tire Size	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15
Hitch Ball Size	2"	2 5/16"	2"	2 5/16"	2"	2 5/16"	2"	2 5/16"	2 5/16"	2 5/16"
Curb Weight (#)	1,100	1,500	1,220	1,620	1,340	1,740	1,460	1,860	2,010	2,130
Hitch Weight (#)	110	125	150	165	200	215	250	265	315	365
GVWR (#)	2,000	2,000	3,500	7,000	3,500	7,000	3,500	7,000	7,000	7,000
Payload Capacity (#)	900	500	2,280	5,380	2,160	5,260	2,040	5,140	4,990	4,870
Rear Doors	Double	Double	Double	Double	Double	Double	Double	Double	Double	Double
Opening Width	62"	62"	62"	62"	62"	62"	62"	62"	62"	62"
Opening Height	59 1/2"	65 1/2"	59 1/2"	65 1/2"	59 1/2"	65 1/2"	59 1/2"	65 1/2"	65 1/2"	65 1/2"
Exterior	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth
Floor (24" O.C.)	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech
Sidewalls (16" O.C.)	3/16" Luan	3/8" Plywood	3/16" Luan	3/8" Plywood	3/16" Luan	3/8" Plywood	3/16" Luan	3/8" Plywood	3/8" Plywood	3/8" Plywood

Additional Standard Features found on all models

- * Fiberglass Front Cap
- * ICC Lighting
- * Safety Chains
- * Safety Breakaway Kit on Electric Brake Units
- * 16" On-Center Wall Studs
- * Brushed Aluminum Fenders
- * Camlocked Rear Doors
- * Seamless Aluminum Roof = .019"
= .023 on Widebody
- * Steel Frame Base = 11 GAUGE = 1/8"
Roof = 16 GAUGE = 1/16"
Sidewalls = 18 GAUGE = 3/64"

ADD 100# FOR LIGHT WEIGHT RAMP

ADD 200# FOR A SPRING ASSISTED RAMP

ADD 25# FOR EVERY 6" ADDITIONAL HEIGHT

SPING AXLE ARE 1" TALLER THAN TORSION