

7' Gooseneck Standard Specifications

	<u>7 X 20</u>	<u>7 X 22</u>	<u>7 X 24</u>	<u>7 X 26</u>	<u>7 X 28</u>	<u>7 X 30</u>	<u>7 X 32</u>
Overall Length	21'	23'	25'	27'	29'	31'	33'
Width	94"	94"	94"	94"	94"	94"	94"
Height	102"	102"	102"	102"	102"	102"	102"
Interior Length	20' 8"	22' 8"	24' 8"	26' 8"	28' 8"	30' 8"	32' 8"
Width (96"/widebody)	81"	81"	81"	81"	81"	81"	81"
Height	78"	78"	78"	78"	78"	78"	78"
Bulkhead Height	44"	44"	44"	44"	44"	44"	44"
Platform Height	21"	21"	21"	21"	21"	21"	21"
Pin Height	43"	43"	43"	43"	43"	43"	43"
Axles	Torsion	Torsion	Torsion	Torsion	Torsion	Torsion	Torsion
Brakes	Electric	Electric	Electric	Electric	Electric	Electric	Electric
Frame	2" x 6"	2" x 6"	2" x 6"	2" x 6"	2" x 6"	2" x 6"	2" x 6"
Tire Size	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15
Hitch Ball Size	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"
Hitch Height (Coupler retracted)	35"	35"	35"	35"	35"	35"	35"
Curb Weight (#)							
Hitch Weight (#)	0	0	0	0	0	0	0
GVWR (#)	7,000	7,000	7,000	7,000	7,000	7,000	7,000
Payload Capacity (#)	7,000	7,000	7,000	7,000	7,000	7,000	7,000
Rear Doors	Double	Double	Double	Double	Double	Double	Double
Opening Width	74"	74"	74"	74"	74"	74"	74"
Opening Height	71 1/2"	71 1/2"	71 1/2"	71 1/2"	71 1/2"	71 1/2"	71 1/2"
Opening Height w/ Beaver	76"	76"	76"	76"	76"	76"	76"
Exterior	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth
Floor (24" O.C.)	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech
Sidewalls (16" O.C.)	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood

Additional Standard Features found on all models

- * Fiberglass Front Cap
- * ICC Lighting
- * Safety Chains
- * Safety Breakaway Kit on Electric Brake Units
- * 16" On-Center Wall Studs
- * Brushed Aluminum Fenders
- * Camlocked Rear Doors
- * Seamless Aluminum Roof

ADD 240# FOR A SPRING ASSISTED RAMP DOOR