

7' Wide Multi-Purpose Standard Specifications

	7 x 10	7 x 10 TA	7 x 12	7 x 12 TA	7 x 14	7 x 14 TA	7 x 16 TA	7 x 18 TA
Overall Length	14' 5"	14' 5"	16' 5"	16' 5"	18' 5"	18' 5"	20' 5"	22' 5"
Width	94"	94"	94"	94"	94"	94"	94"	94"
Height	95"	95"	95"	95"	95"	95"	95"	95"
Interior Length	10' 9"	10' 9"	12' 9"	12' 9"	14' 9"	14' 9"	16' 9"	18' 9"
Width	81 1/2"	81 1/2"	81 1/2"	81 1/2"	81 1/2"	81 1/2"	81 1/2"	81 1/2"
Height	72"	72"	72"	72"	72"	72"	72"	72"
Platform/Hitch Height	20"	20"	20"	20"	20"	20"	20"	21"
Axles	Spring/Torsion	Spring/Torsion	Spring/Torsion	Spring/Torsion	Spring/Torsion	Spring/Torsion	Spring/Torsion	Spring/Torsion
Brakes	N/A	Electric	N/A	Electric	N/A	Electric	Electric	Electric
Frame	2" x 5"	2" x 5"	2" x 5"	2" x 5"	2" x 5"	2" x 5"	2" x 5"	2" x 6"
Tire Size	P235/75R15	P235/75R15	P235/75R15	P235/75R15	P235/75R15	P235/75R15	P235/75R15	P235/75R15
Hitch Ball Size	2"	2 5/16"	2"	2 5/16"	2"	2 5/16"	2 5/16"	2 5/16"
Curb Weight (#)	1500	1860	1660	2020	1820	2180	2340	2540
Hitch Weight (#)	220	245	235	260	250	275	290	310
GVWR (#)	3,500	7,000	3,500	7,000	3,500	7,000	7,000	7,000
Payload Capacity (#)	2,000	5,140	1,840	4,980	1,680	4,820	4,660	4,460
Rear Doors	Double	Double	Double	Double	Double	Double	Double	Double
Opening Width	74"	74"	74"	74"	74"	74"	74"	74"
Opening Height	65 1/2"	65 1/2"	65 1/2"	65 1/2"	65 1/2"	65 1/2"	65 1/2"	65 1/2"
Exterior	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth
Floor (24" O.C.)	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech
Sidewalls (16" O.C.)	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood

Additional Standard Features found on all models

- * Fiberglass Front Cap
- * ICC Lighting
- * Safety Chains
- * Safety Breakaway Kit on Electric Brake Units
- * 16" On-Center Wall Studs
- * Brushed Aluminum Fenders
- * Camlocked Rear Doors
- * Seamless Aluminum Roof = .019"
= .023 on Widebody
- * Steel Frame Base = 11 GAUGE = 1/8"
 Roof = 16 GAUGE = 1/16"
 Sidewalls = 18 GAUGE = 3/64"

ADD 240# FOR A SPRING ASSISTED RAMP DOOR AND SUBTRAC

7 x 20 TA	7 x 22 TA
24' 5"	26' 5"
94"	94"
95"	95"
20' 9"	22' 9"
81 1/2"	81 1/2"
72"	72"
21"	21"
Spring/Torsion	Spring/Torsion
Electric	Electric
2" x 6"	2" x 6"
P235/75R15	P235/75R15
2 5/16"	2 5/16"
2710	2880
330	350
7,000	7,000
4,290	4,120
Double	Double
74"	74"
65 1/2"	65 1/2"
.030 Smooth	.030 Smooth
3/4" Advantech	3/4" Advantech
3/8" Plywood	3/8" Plywood

CT 100# HITCH WEIGHT