8' Gooseneck Standard Specifications

	8 X 22	8 X 24	8 X 26	8 X 28	8 X 30	8 X 32	8 X 34	8 X 36	8 X 38	8 X 40	8 X 42	8 X 44	8 X 46	8 X 48
Overall Length	23' 3"	25' 3"	27' 3"	29' 3"	31' 3"	33' 3"	35' 3"	37' 3"	39' 3"	41' 3"	43' 3"	45' 3"	47' 3"	49' 3"
Width (96"widebody)	100"/102"	100"/102"	100"/102"	100"/102"	100"/102"	100"/102"	100"/102"	100"/102"	100"/102"	100"/102"	100"/102"	100"/102"	100"/102"	100"/102"
Height (96"widebody)	105"/108"	105"/108"	105"/108"	105"/108"	105"/108"	105"/108"	105"/108"	107"/108"	107"/108"	107"/108"	107"/108"	107"/108"	109"/110"	109"/110"
Interior Length	22' 11"	24' 11"	26' 11"	28' 11"	30' 11"	32' 11"	34' 11"	36' 11"	38' 11"	40' 11"	42' 11"	44' 11"	46' 11"	48' 11"
Width (96"widebody)	93"/97"	93"/97"	93"/97"	93"/97"	93"/97"	93"/97"	93"/97"	93"/97"	93"/97"	93"/97"	93"/97"	93"/97"	93"/97"	93"/97"
Height	79"	79"	79"	79"	79"	79"	79"	79"	79"	79"	79"	79"	79"	79"
Bulkhead Height	44"	44"	44"	44"	44"	44"	44"	44"	44"	44"	44"	44"	44"	44"
Platform Height	21"	21"	21"	21"	21"	21"	21"	23"	23"	23"	23"	23"	25"	25"
Dip Height	43"	43"	43"	43"	43"	43"	43"	45"	45"	45"	45"	45"	47"	47"
Axles	Torsion	Torsion	Torsion	Torsion	Torsion	Torsion	Torsion	Torsion	Torsion	Torsion	Torsion	Torsion	Torsion	Torsion
Brakes	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric
Frame	3" x 6"	3" x 6"	3" x 6"	3" x 6"	3" x 6"	3" x 6"	3" x 6"	3" x 8"	3" x 8"	3" x 8"	3" x 8"	3" x 8"	3" x 10"	3" x 10"
Tire Size	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15
Hitch Ball Size	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"
Hitch Height (Coupler retracted)	35"	35"	35"	35"	35"	35"	35"	37"	37"	37"	37"	37"	39"	39"
Curb Weight (#)	3700	4000	4250	4550	4700	4900	5100	5300	5650	5900	6230	6500	6750	7000
Hitch Weight (#)	938	1000	1063	1125	1175	1225	1275	1325	1413	1488	1558	1625	1688	1750
GVWR (#)	9,990	9,990	9,990	9,990	9,990	9,950	9,990	9,990	9,990	9,990	9,990	9,990	9,990	9,950
Payload Capacity (#)	6,240	5,990	5,740	5,490	5,290	5,050	4,990	4,690	4,340	4,040	3,760	3,490	3,240	2,990
Rear Doors	Double	Double	Double	Double	Double	Double	Double	Double	Double	Double	Double	Double	Double	Double
Opening Width	86"/60"	86"/60"	86"/60"	86"/60"	86"/60"	86"/60"	86"/60"	86"/60"	86"/60"	86"/60"	86"/60"	86"/60"	86"/60"	86"/60"
Opening Height	71 1/2"	71 1/2"	71 1/2"	71 1/2"	71 1/2"	71 1/2"	71 1/2"	71 1/2"	71 1/2"	71 1/2"	71 1/2"	71 1/2"	71 1/2"	71 1/2"
Opening Height w/ Beaver	75"	75"	75"	75"	75"	75"	75"	75"	75"	75"	75"	75"	75"	75"
Exterior	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth
Floor (24" O.C.)	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech
Sidewalls (16" O.C.)	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood

Additional Standard Features found on all models

- Fiberglass Front Cap
- ICC Lighting
- Safety Chains
- Safety Breakaway Kit on Electric Brake Units
- 16" On-Center Wall Studs
- Brushed Aluminum Fenders
- Camlocked Rear Doors
- Seamless Aluminum Roof

ADD 240# FOR A SPRING ASSISTED RAMP DOOR