

8' Wide Multi-Purpose Standard Specifications

	8 X 12	8 X 14	8 X 16	8 X 18	8 X 20	8 X 22	8 X 24	8 X 26
Overall Length	16' 9"	18' 9"	20' 9"	22' 9"	24' 9"	26' 9"	28' 9"	30' 9"
Width (96"/widebody)	100"/102"	100"/102"	100"/102"	100"/102"	100"/102"	100"/102"	100"/102"	100"/102"
Height (96"/widebody)	105"/106"	105"/106"	105"/106"	105"/106"	105"/106"	105"/106"	105"/106"	105"/106"
Interior Length	12' 11"	14' 11"	16' 11"	18' 11"	20' 11"	22' 11"	24' 11"	26' 11"
Width (96"/widebody)	93"/97"	93"/97"	93"/97"	93"/97"	93"/97"	93"/97"	93"/97"	93"/97"
Height	78"	78"	78"	78"	78"	78"	78"	78"
Platform/Hitch Height	21"	21"	21"	21"	21"	21"	21"	21"
Axles	Spring/Torsion	Spring/Torsion	Spring/Torsion	Spring/Torsion	Spring/Torsion	Spring/Torsion	Spring/Torsion	Spring/Torsion
Brakes	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric
Frame	2" x 6"	2" x 6"	2" x 6"	2" x 6"	2" x 6"	2" x 6"	2" x 6"	2" x 6"
Tire Size	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15
Hitch Ball Size	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"
Curb Weight (#)	2220	2430	2640	2850	3060	3270	3480	3780
Car Carrier (#)	2600	2800	3000	3220	3440	3660	3890	4260
Hitch Weight (#)	230	250	270	290	310	340	360	400
GVWR (#)	7,000	7,000	7,000	7,000	7,000	7,000	7,000	9,990
Payload Capacity (#)	4,780	4,570	4,360	4,150	3,940	3,730	3,520	6,210
Rear Doors	Double	Double	Double	Double	Double	Double	Double	Double
Opening Width	86"/90"	86"/90"	86"/90"	86"/90"	86"/90"	86"/90"	86"/90"	86"/90"
Opening Height	71 1/2"	71 1/2"	71 1/2"	71 1/2"	71 1/2"	71 1/2"	71 1/2"	71 1/2"
Opening Height w/ Beaver	76"	76"	76"	76"	76"	76"	76"	76"
Exterior	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth
Floor (24" O.C.)	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech
Sidewalls (16" O.C.)	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood

Additional Standard Features found on all models

- * Fiberglass Front Cap
- * ICC Lighting
- * Safety Chains
- * Safety Breakaway Kit on Electric Brake Units
- * 16" On-Center Wall Studs
- * Brushed Aluminum Fenders
- * Camlocked Rear Doors
- * Seamless Aluminum Roof = .019"
= .023 on Widebody
- * Steel Frame Base = 11 GAUGE = 1/8"
Roof = 16 GAUGE = 1/16"
Sidewalls = 18 GAUGE = 3/64"

ADD 240# FOR A SPRING ASSISTED RAMP DOOR

Hitch Weights vary due to options and load placement

Widebody Option adds 2.5% to Curbweight

6000# axle upgrade adds 600# to Curbweight

8 X 28	8 X 30	8 X 32
32' 9"	34' 9"	36' 9"
100"/102"	100"/102"	100"/102"
105"/106"	107"/108"	107"/108"
28' 11"	30' 11"	32' 11"
93"/97"	93"/97"	93"/97"
78"	78"	78"
21"	23"	23"
Spring/Torsion	Spring/Torsion	Spring/Torsion
Electric	Electric	Electric
2" x 6"	2" x 8"	2" x 8"
ST225/75D15	ST225/75D15	ST225/75D15
2 5/16"	2 5/16"	2 5/16"
4080	4530	4980
4560	5010	5460
430	470	500
9,990	9,990	9,990
5,910	5,460	5,010
Double	Double	Double
86"/90"	86"/90"	86"/90"
71 1/2"	71 1/2"	71 1/2"
76"	78"	78"
.030 Smooth	.030 Smooth	.030 Smooth
3/4" Advantech	3/4" Advantech	3/4" Advantech
3/8" Plywood	3/8" Plywood	3/8" Plywood