

STE Car Carrier Specifications

	8 X 16	8 X 18	8 X 20	8 X 22	8 X 24	8 X 26	8 X 28	8 X 30	8 X 32
Overall Length	20' 9"	22' 9"	24' 9"	26' 9"	28' 9"	30' 9"	32' 9"	34' 9"	36' 9"
Width (96"/widebody)	100"/102"	100"/102"	100"/102"	100"/102"	100"/102"	100"/102"	100"/102"	100"/102"	100"/102"
Height (96"/widebody)	105"/106"	105"/106"	105"/106"	105"/106"	105"/106"	105"/106"	105"/106"	107"/108"	107"/108"
Interior Length	16' 11"	18' 11"	20' 11"	22' 11"	24' 11"	26' 11"	28' 11"	30' 11"	32' 11"
Width (96"/widebody)	93"/97"	93"/97"	93"/97"	93"/97"	93"/97"	93"/97"	93"/97"	93"/97"	93"/97"
Height	78"	78"	78"	78"	78"	78"	78"	78"	78"
Platform\ Hitch Height	21"	21"	21"	21"	21"	21"	21"	23"	23"
Axles	Spring	Spring	Spring	Spring	Spring	Spring	Spring	Spring	Spring
Brakes	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric
Frame	2" x 6"	2" x 6"	2" x 6"	2" x 6"	2" x 6"	2" x 6"	2" x 6"	2" x 8"	2" x 8"
Tire Size	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15
Hitch Ball Size	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"
Curb Weight (#)	3000	3220	3440	3660	3890	4260	4560	5010	5460
Car Carrier Hitch Weight(#)	170	190	210	250	270	320	350	400	430
GVWR (#)	7,000	7,000	7,000	7,000	7,000	9,990	9,990	9,990	9,990
Payload Capacity (#)	4,000	3,780	3,560	3,340	3,110	5,730	5,430	4,980	4,530
Ramp Door w/ Beavertail	Std	Std	Std	Std	Std	Std	Std	Std	Std
Opening Width	86"/90"	86"/90"	86"/90"	86"/90"	86"/90"	86"/90"	86"/90"	86"/90"	86"/90"
Opening Height	76"	76"	76"	76"	76"	76"	76"	78"	78"
Exterior	.024 Smooth	.024 Smooth	.024 Smooth	.024 Smooth	.024 Smooth	.024 Smooth	.024 Smooth	.024 Smooth	.024 Smooth
Floor (24" O.C.)	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech
Sidewalls (16" O.C.)	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood

Additional Standard Features found on all models

- * Fiberglass Front Cap
- * ICC Lighting
- * Safety Chains
- * Safety Breakaway Kit on Electric Brake Units
- * 16" On-Center Wall Studs
- * Brushed Aluminum Fenders
- * Seamless Aluminum Roof
 - = .019"
 - = .023 on Widebody
- * Steel Frame Base
 - = 11 GAUGE = 1/8"
 - Roof = 16 GAUGE = 1/16"
 - Sidewalls = 18 GAUGE = 3/64"

Hitch Weights vary due to options and load placement
 Widebody Option adds 2.5% to Curbweight
 6000# axle upgrade adds 600# to Curbweight