

STE Single Axle Cargo Hauler Specifications

	<u>5 x 8</u>	<u>5 x 10</u>	<u>6 x 10</u>	<u>6 x 12</u>	<u>7 x 10</u>	<u>7 x 12</u>	<u>7 x 14</u>
Overall Length	12' 4"	14' 4"	14' 5"	16' 5"	14' 5"	16' 5"	18' 5"
Width	81"	81"	93"	93"	94"	94"	94"
Height	79"	79"	87"	87"	95"	95"	95"
Interior Length	8' 6"	10' 6"	10' 8"	12' 8"	10' 9"	12' 9"	14' 9"
Width	57 1/2"	57 1/2"	69 1/2"	69 1/2"	81 1/2"	81 1/2"	81 1/2"
Height	60"	60"	66"	66"	72"	72"	72"
Platform/Hitch Height	18"	18"	19"	19"	20"	20"	20"
Axles	Spring	Spring	Spring	Spring	Spring	Spring	Spring
Brakes	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Frame	2" x 3"	2" x 3"	2" x 4"	2" x 4"	2" x 5"	2" x 5"	2" x 5"
Tire Size	ST205/75D14	ST205/75D14	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15
Hitch Ball Size	2"	2"	2"	2"	2"	2"	2"
Curb Weight (#)	900	960	1,220	1,340	1500	1660	1820
Hitch Weight (#)	120	130	150	200	220	235	250
GVWR (#)	3,500	3,500	3,500	3,500	3,500	3,500	3,500
Payload Capacity (#)	2,600	2,540	2,280	2,160	2,000	1,840	1,680
Rear Doors	Double	Double	Double	Double	Double	Double	Double
Opening Width	50"	50"	62"	62"	74"	74"	74"
Opening Height	53 1/2"	53 1/2"	59 1/2"	59 1/2"	65 1/2"	65 1/2"	65 1/2"
Exterior	.024 Smooth	.024 Smooth	.024 Smooth	.024 Smooth	.024 Smooth	.024 Smooth	.024 Smooth
Floor (24" O.C.)	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech
Sidewalls (16" O.C.)	3/16" Luan	3/16" Luan	3/16" Luan	3/16" Luan	3/16" Luan	3/16" Luan	3/16" Luan

Additional Standard Features found on all models

- * Fiberglass Front Cap
- * ICC Lighting
- * Safety Chains
- * Safety Breakaway Kit on Electric Brake Units
- * 16" On-Center Wall Studs
- * Brushed Aluminum Fenders
- * Camlocked Rear Doors
- * Seamless Aluminum Roc = .019"
 - = .023 on Widebody
- * Steel Frame Base = 11 GAUGE = 1/8"
 - Roof = 16 GAUGE = 1/16"
 - Sidewalls = 18 GAUGE = 3/64"

ADD 100# FOR LIGHT WEIGHT RAMP
 ADD 200# FOR A SPRING ASSISTED RAMP
 ADD 25# FOR EVERY 6" ADDITIONAL HEIGHT