

STE Single Axle Motorcycle Hauler Specifications

	5 x 10	6 x 8	6 x 10	6 x 12	7 x 10
Overall Length	14' 4"	12' 5"	14' 5"	16' 5"	14' 5"
Width	81"	93"	93"	93"	94"
Height	79"	87"	87"	87"	95"
Interior Length	10' 6"	8' 8"	10' 8"	12' 8"	10' 9"
Width	57 1/2"	69 1/2"	69 1/2"	69 1/2"	81 1/2"
Height	60"	66"	66"	66"	72"
Platform/Hitch Height	18"	19"	19"	19"	20"
Axles	Spring	Spring	Spring	Spring	Spring
Brakes	N/A	N/A	N/A	N/A	N/A
Frame	2" x 3"	2" x 4"	2" x 4"	2" x 4"	2" x 5"
Tire Size	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15
Hitch Ball Size	2"	2"	2"	2"	2"
Curb Weight (#)	1060	1,200	1,320	1,440	1600
Hitch Weight (#)	120	100	140	190	210
GVWR (#)	3,500	3,500	3,500	3,500	3,500
Payload Capacity (#)	2,440	2,300	2,180	2,060	1,900
Rear Doors	Light Ramp	Light Ramp	Light Ramp	Light Ramp	Light Ramp
Opening Width	50"	62"	62"	62"	74"
Opening Height	53 1/2"	59 1/2"	59 1/2"	59 1/2"	65 1/2"
Exterior	.024 Smooth	.024 Smooth	.024 Smooth	.024 Smooth	.024 Smooth
Floor (24" O.C.)	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech
Sidewalls (16" O.C.)	3/16" Luan	3/16" Luan	3/16" Luan	3/16" Luan	3/16" Luan

Additional Standard Features found on all models

- * Fiberglass Front Cap
- * ICC Lighting
- * Safety Chains
- * Safety Breakaway Kit on Electric Brake Units
- * 16" On-Center Wall Studs
- * Brushed Aluminum Fenders
- * Camlocked Rear Doors
- * Seamless Aluminum Roof = .019"
= .023 on Widebody
- * Steel Frame Base = 11 GAUGE = 1/8"
Roof = 16 GAUGE = 1/16"
Sidewalls = 18 GAUGE = 3/64"

ADD 100# FOR A SPRING ASSISTED RAMP

ADD 25# FOR EVERY 6" ADDITIONAL HEIGHT