

## STE Tandem Axle Motorcycle Hauler Specifications

	6 x 12	6 x 14	7 x 12	7 x 14	7 x 16	7 x 18
Overall Length	16' 5"	18' 5"	16' 5"	18' 5"	20' 5"	22' 5"
Width	93"	93"	94"	94"	94"	94"
Height	94"	94"	96"	96"	96"	97"
Interior Length	12' 8"	14' 8"	12' 9"	14' 9"	16' 9"	18' 9"
Width	69 1/2"	69 1/2"	81 1/2"	81 1/2"	81 1/2"	81 1/2"
Height	72"	72"	72"	72"	72"	72"
Platform/Hitch Height	20"	20"	21"	21"	21'	22"
Axles	Spring	Spring	Spring	Spring	Spring	Spring
Brakes	Single Electric	Single Electric	Single Electric	Single Electric	Single Electric	Single Electric
Frame	2" x 4"	2" x 4"	2" x 5"	2" x 5"	2" x 5"	2" x 6"
Tire Size	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15
Hitch Ball Size	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"
Curb Weight (#)	1,840	2,240	2220	2380	2540	2740
Hitch Weight (#)	205	255	240	255	270	290
GVWR (#)	7,000	7,000	7,000	7,000	7,000	7,000
Payload Capacity (#)	5,160	4,760	4,780	4,620	4,460	4,260
Rear Doors	Light Ramp	Light Ramp	SA Ramp	SA Ramp	SA Ramp	SA Ramp
Opening Width	62"	62"	74"	74"	74"	74"
Opening Height	65 1/2"	65 1/2"	65 1/2"	65 1/2"	65 1/2"	65 1/2"
Exterior	.024 Smooth	.024 Smooth	.024 Smooth	.024 Smooth	.024 Smooth	.024 Smooth
Floor (24" O.C.)	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech
Sidewalls (16" O.C.)	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood

### Additional Standard Features found on all models

- \* Fiberglass Front Cap
- \* ICC Lighting
- \* Safety Chains
- \* Safety Breakaway Kit on Electric Brake Units
- \* 16" On-Center Wall Studs
- \* Brushed Aluminum Fenders
- \* Camlocked Rear Doors
- \* Seamless Aluminum Roof = .019"
- = .023 on Widebody
- \* Steel Frame Base = 11 GAUGE = 1/8"
- Roof = 16 GAUGE = 1/16"
- Sidewalls = 18 GAUGE = 3/64"

ADD 100# FOR A SPRING ASSISTED RAMP  
 ADD 30# FOR EVERY 6" ADDITIONAL HEIGHT